



High Performance Industrial Servo Voltage Stabiliser

Unique Features

- #. Fully Automatic
- #. Servo Mechanism
- #. Wide voltage Range
- #. Electronic Intelligent Protection
- #. Surge Suppressor

SPECIFICATIONS

THREE PHASE

- Input** : 300V to 460V Normal Range
250V to 460V Extended Range
- Frequency** : 50Hz \pm 3Hz
- Termination** : 4 Wire System by Terminal block
- Output** : 400 \pm 1% Tunable between 380V to 420V
- Frequency** : Same as Input wave form Distortion nil
Correction speed 35V/ Second
- Protections** : High /Low voltage cutoff , OverLoad, Single Phase, Preventor Manual by pass.
- Rating** : 3KVA to 50KVA Air Cooled above 50 KVA Oil Cooled

SPECIFICATIONS SINGLE PHASE

- Input** : 160V to 260V Normal
140V to 270V Extended Range
- Output** : 230 \pm 1% Tunable Between 210-240V
- Rating** : 1KVA to 25KVA



1 Phase Domestic



3 Phase Air Cooled



3Phase Oil cooled

Mfg By

Powertron Engineering Services

No, 39/2-7, Kalyani Garden
 N R Colony, B S K 1st Stage
 Bangalore - 560050. Ph. 9845340636,
 9880102939, 9663548168

E-mail. girish.powertron@gmail.com
 info@powertronindia.in

Web site : www.powertronindia.in